

EOLO HT 180°C



灰色软管，聚酯织物覆阻燃PU涂层，夹层焊接螺旋钢丝增强 原材料符合UL 94(V(TM)-0,M1)，NF P 92-503和NF EN2310(FAR25-853-a)阻燃等级；不含硅。

• 民用和海军空调工厂、通风系统中，抽吸烟雾，蒸汽，粉末，气体等。

Grey hose made in flame resistant TPU coated polyester fabric and reinforced by steel helix welded between the two layers. The material is flame retardant V(TM)-0 according to UL 94, grade M1 according to NF P 92-503 and grade FAR25-853-a, according to NF EN 2310. Silicon free.

• Civil and naval conditioning plants, ventilation systems, suction of welding fumes, vapours, powders, gas.



技术参数 / Technical data

代码	外径	重量	弯曲半径	每卷长度	体积
Code	Ins. Ø	Weight	Bending	Coil lgth.	Vol.
	mm	g/m	mm	m	m³
H1 01 040.0 000.0	40*	125	20	10	0,002
H1 01 045.0 000.0	45*	140	22,5	10	0,002
H1 01 051.0 000.0	51*	150	25,5	10	0,003
H1 01 055.0 000.0	55*	165	27,5	10	0,003
H1 01 060.0 000.0	60*	175	30	10	0,004
H1 01 063.0 000.0	63*	185	31,5	10	0,004
H1 01 065.0 000.0	65*	190	32,5	10	0,005
H1 01 070.0 000.0	70*	185	35	10	0,005
H1 01 076.0 000.0	76*	200	38	10	0,006
H1 01 080.0 000.0	80*	210	40	10	0,007
H1 01 090.0 000.0	90*	240	45	10	0,009
H1 01 102.0 000.0	102*	310	51	10	0,011
H1 01 110.0 000.0	110*	330	55	10	0,013
H1 01 115.0 000.0	115*	345	57,5	10	0,014
H1 01 120.0 000.0	120*	360	60	10	0,015
H1 01 127.0 000.0	127*	385	63,5	10	0,017
H1 01 130.0 000.0	130*	390	65	10	0,018
H1 01 140.0 000.0	140*	420	70	10	0,021
H1 01 152.0 000.0	152*	460	76	10	0,024
H1 01 160.0 000.0	160*	470	80	10	0,027
H1 01 180.0 000.0	180*	525	90	10	0,034
H1 01 203.0 000.0	203*	595	101,5	10	0,043
H1 01 228.0 000.0	228*	665	114	10	0,054
H1 01 254.0 000.0	254*	910	127	10	0,067
H1 01 279.0 000.0	279*	1000	139,5	10	0,080
H1 01 305.0 000.0	305*	1095	152,5	10	0,096
H1 01 315.0 000.0	315*	1130	157,5	10	0,102
H1 01 330.0 000.0	330*	1180	165	10	0,112
H1 01 356.0 000.0	356*	1275	178	10	0,130
H1 01 406.0 000.0	406*	1455	203	10	0,168

*如有需求, 请与我们的销售办公室联系以获得更多的信息和数据/ *Available on request, contact our sales office for more info and quantities

以上技术数据均在温度23°C，50%湿度下测量 / The technical data here reported were measured at 23°C with 50% humidity