

VULCANO PU H 09 ESTERE




+90° C
-40° C
峰值/peaks
125° C

半透明聚酯型聚氨酯软管，包塑镀铜钢丝螺旋加强。TPU包塑使得螺旋钢丝与管壁更好的粘合，恒定壁厚0.9mm，适合于要求非常好的耐磨性的重型应用。可定制耐微生物型或永久性抗静电（R < 109欧姆/米）版本，也可通过将软管两端螺旋钢丝接地来导电

- 适用于塑料、木工、陶瓷、除尘等行业中抽吸颗粒、磨料粉、粒料、锯末。

包塑镀铜螺旋钢丝
TPU coated copper colored steel spiral



聚酯型聚氨酯材质 / Ester based TPU hose



Translucent ester based Polyurethane hose, reinforced with a TPU coated copper colored steel spiral. The TPU-coated spiral allows a better adhesion. Constant wall thickness 0,9 mm through all the diameter range; flexible and suitable for heavy duty applications where a very good abrasion resistance is required. On request it can be made in microbes resistant version or with permanent antistatic 10^9 Ohm/metre material. It can be made conductive by earthing the steel spiral.

- Suction of granules, abrasive powders, pellets, sawdust. Suitable to be used in plastic, woodworking, ceramic, dust extraction industries.

技术参数 / Technical data

代码 Code	内径 Ø Int.	最小壁厚 Min wall th.	重量 Weight	弯曲半径 Bending	耐负压 Vac.	每卷长度 Coil lgth.	体积 Vol.	桥式卡箍 W2 double bridge W2
	mm	mm	g/m	mm	m H ₂ O	m	m ³	
VB 01 020.0 000.0	20*	0,90	170	25	5,0	20	0,040	-
VB 01 025.0 000.0	25*	0,90	215	30	5,0	20	0,040	-
VB 01 030.0 000.0	30*	0,90	260	35	5,0	20	0,050	-
VB 01 032.0 000.0	32*	0,90	280	35	5,0	20	0,050	-
VB 01 035.0 000.0	35*	0,90	300	40	5,0	20	0,060	-
VB 01 038.0 000.0	38	0,90	290	40	5,0	20	0,060	-
VB 01 040.0 000.0	40	0,90	300	50	5,0	20	0,070	-
VB 01 045.0 000.0	45*	0,90	390	50	5,0	20	0,070	-
VB 01 051.0 000.0	51	0,90	435	60	4,0	20	0,100	-
VB 01 055.0 000.0	55*	0,90	470	65	3,5	20	0,120	-
VB 01 060.0 000.0	60	0,90	510	70	3,0	20	0,130	-
VB 01 063.0 000.0	63	0,90	530	70	3,0	20	0,130	-
VB 01 065.0 000.0	65*	0,90	545	70	3,0	20	0,180	-
VB 01 070.0 000.0	70	0,90	675	80	3,0	20	0,200	-
VB 01 076.0 000.0	76	0,90	730	90	3,0	20	0,240	-
VB 01 080.0 000.0	80	0,90	765	90	3,0	20	0,260	-
VB 01 090.0 000.0	90	0,90	855	100	2,5	20	0,290	F2 W2 076.0 090.0
VB 01 102.0 000.0	102	0,90	965	120	2,0	15	0,320	-
VB 01 110.0 000.0	110*	0,90	1035	130	2,0	15	0,340	-
VB 01 115.0 000.0	115*	0,90	1080	135	1,5	15	0,360	F2 W2 100.0 127.0
VB 01 120.0 000.0	120	0,90	1125	140	1,5	15	0,370	-
VB 01 127.0 000.0	127	0,90	1370	150	1,5	15	0,390	-
VB 01 130.0 000.0	130*	0,90	1405	150	1,5	15	0,400	-
VB 01 140.0 000.0	140	0,90	1505	160	1,0	15	0,640	-
VB 01 150.0 000.0	150*	0,90	1610	170	1,0	15	0,690	F2 W2 130.0 190.0
VB 01 152.0 000.0	152	0,90	1630	170	1,0	15	0,700	-
VB 01 160.0 000.0	160	0,90	1715	180	1,0	15	0,730	-
VB 01 180.0 000.0	180	0,90	1720	210	0,5	15	0,970	-
VB 01 200.0 000.0	200	0,90	1905	230	0,5	15	1,080	-
VB 01 203.0 000.0	203	0,90	1930	230	0,5	15	1,090	-
VB 01 220.0 000.0	220*	0,90	2090	260	0,3	10	1,180	F2 W2 200.0 230.0
VB 01 228.0 000.0	228*	0,90	2160	260	0,3	10	1,220	-
VB 01 250.0 000.0	250*	0,90	2365	290	0,3	10	1,330	-
VB 01 254.0 000.0	254	0,90	2400	290	0,3	10	1,350	-
VB 01 279.0 000.0	279*	0,90	2870	320	0,2	10	1,480	-
VB 01 300.0 000.0	300*	0,90	3080	350	0,2	10	1,590	F2 W2 250.0 330.0
VB 01 305.0 000.0	305	0,90	3130	350	0,2	10	1,610	-
VB 01 315.0 000.0	315*	0,90	3230	350	0,2	10	1,660	-
VB 01 350.0 000.0	350*	0,90	4075	410	0,1	可定制 (最长10米) /On request (max 10m) straight pieces A	-	-
VB 01 356.0 000.0	356*	0,90	4145	410	0,1	可定制 (最长10米) /On request (max 10m) straight pieces A	-	F2 W2 350.0 410.0
VB 01 400.0 000.0	400*	0,90	4645	N.D.	0,1	可定制 (最长10米) /On request (max 10m) straight pieces A	-	-
VB 01 450.0 000.0	450*	0,90	6535	N.D.	0,1	可定制 (最长6米) /On request (max 6m)	-	-

* 如有需求，请与我们的销售办公室联系以获得更多的信息和数据 / * Available on request, contact our sales office for more info and quantities

以上技术数据均在温度23°C，50%湿度下测量 / The technical data here reported were measured at 23°C with 50% humidity

防静电版本在第 28 页 / Available also in the electrical conductive version, pag. 28