

EOLO HT 450°C



双层特殊耐高温硅胶外涂层，玻璃纤维织物内层，镀锌钢螺旋增强 瞬间可耐高温550°C，不易燃。良好的轴向压缩性能（压缩比6：1）。

- 主要适用于多种行业高温空气/烟雾/气体的抽吸和排放，如窑炉、炼钢厂、引擎装置以及航空工业中的热空气、废气及烟雾等。

2 ply special high temperature silicone coated glass fabric outside, raw glass inside, reinforced with an external galvanized steel "Clamp profile". Resistant to high temperature peaks up to 550°C. Hardly inflammable. Good axial compressibility 6:1.

- *Mainly suitable as extraction and blowing hose of high temperature air/fumes/gasses in many industries: hot air, exhaust gas and fumes in suction plants, furnace construction, iron production and steelworks, vehicle and engine constructions, aircraft industry.*



技术参数 / Technical data

代码 Code	内径 Ins. Ø	重量 Weight	耐负压 Vac.	弯曲半径 Bending	每卷长度 Coil lgth.
	mm	g/m	m H ₂ O	mm	m
H5 01 050	50	600	4,78	30	6
H5 01 060	60	700	2,83	36	6
H5 01 065	65	800	2,41	39	6
H5 01 070	70	900	2,08	42	6
H5 01 075	75	1000	1,81	45	6
H5 01 080	80	1000	1,59	48	6
H5 01 090	90	1200	1,25	54	6
H5 01 100	100	1300	1,02	60	6
H5 01 110	110	1300	0,84	66	6
H5 01 120	120	1400	0,74	72	6
H5 01 125	125	1400	0,65	75	6
H5 01 130	130	1600	0,6	78	6
H5 01 140	140	1600	0,52	84	6
H5 01 150	150	1800	0,44	90	6
H5 01 160	160	1800	0,39	96	6
H5 01 170	170	2000	0,35	102	6
H5 01 175	175	2100	0,33	105	6
H5 01 180	180	2100	1,73	108	6
H5 01 200	200	2300	1,52	120	6
H5 01 215	215	2400	1,32	129	6
H5 01 225	225	2400	1,22	135	6
H5 01 250	250	2600	1,02	175	6
H5 01 275	275	2700	0,81	193	6
H5 01 300	300	2750	0,81	210	6
H5 01 315	315	2800	0,61	221	6
H5 01 325	325	2900	0,61	228	6
H5 01 350	350	3050	0,51	245	6
H5 01 375	375	3200	0,51	263	6
H5 01 400	400	3400	0,51	280	6
H5 01 450	450	4000	0,40	360	6
H5 01 500	500	4500	0,40	400	6
H5 01 600	600	5600	0,40	480	3
H5 01 700	700	6600	0,30	560	3
H5 01 800	800	7600	0,20	640	3
H5 01 900	900	8600	0,20	720	3

如有需求, 请与我们的销售办公室联系以获得更多的信息和数据 / *Available on request, contact our sales office for more info and quantities

以上技术数据均在温度23°C，50%湿度下测量 / The technical data here reported were measured at 23°C with 50% humidity